

Thermaltake

Napajanje 650W Thermaltake Smart BM2 80+ Bronze/Modular, PS-SPD- 0650MNFABE-1

Dostupnost: NA STANJU

MP cena: 10.190,00 din

Šifra proizovda: 29568

8.990,00 din

Ušteda: 1.200,00 din

Opis

P/N PS-SPD-0650MNFABU-1

WATTS 650W

RGB FAN No

MODEL SP-650AH3CCB-B | SP-650AH3CLB-B

TYPE ATX 12V v2.4 and EPS v2.92

MAX. OUTPUT CAPACITY 650W

COLOR Black

DIMENSION (W / H / D) 150mm(W) x 86mm(H) x 160mm(D)

PFC (POWER FACTOR CORRECTION) Active PFC

POWER GOOD SIGNAL 100-500 msec

HOLD UP TIME > 12msec at 80% of full load at 230Vac input

INPUT CURRENT 10A max. | 6 – 12A

INPUT FREQUENCY RANGE 47Hz -63Hz

INPUT VOLTAGE 100V-240V~

OPERATING TEMPERATURE 0°C to +40°C | +5°C to +40°C

OPERATING HUMIDITY 20% to 90%,non-condensing | 20% to 85%,non-condensing

STORAGE TEMPERATURE -20 °C to +70 °C | -40 °C to +55 °C

STORAGE HUMIDITY 5% to 95%, non-condensing | 10% to 95%, non-condensing

COOLING SYSTEM 140mm Fan: 2300 R.P.M. ± 10%

EFFICIENCY Meet 80 PLUS®Bronze at 115Vac input.

MTBF 100,000 hrs minimum

SAFETY APPROVAL cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC

PCI-E 6+2PIN 4

PROTECTION OVP ,OPP, OCP, OTP

Specifikacija